



NAXOS

VENTILATED PELLET STOVE



ENERGY LABELLING



EN 14785-2006

ECO DESIGN

2022



NAXOS		8
ENERGY CLASS		A+
DIMENSIONS (LxPxH)	cm	61x52x102
WEIGHT	kg	102
NOMINAL INPUT (min.-max.)	kW	2,45 - 8,0
NOMINAL OUTPUT (min.-max.)	kW	2,4 - 7,64
EFFICIENCY AT NOMINAL OUTPUT (min.-max.)	%	97,89 - 95,59
MINIMUM DRAUGHT AT THE CHIMNEY BASE	Pa	12
SMOKE OUTLET Ø	mm Ø	80
AIR INTAKE DIAMETER	mm Ø	50
PELLET RESERVOIR CONTENT	kg	20
AVERAGE CONSUMPTION (min.-max.)	kg/h	0,51 - 1,65
Nominal ELECTRIC ABSORPTION	W	87
ELECTRIC ABSORPTION at the ignition stage	W	300
HEATING VOLUME	m ³	195
NOISINESS	dB	35 / 55

Slim line pellet stove. Rounded side panels with cast iron top with a pleasant and elegant surface finish. The “Hermetic” technology (room sealed) makes the NAXOS stove a very versatile product.

PLUS PRODUCT



VENTILATED STOVE



HERMETIC



CERAMIC GLASS



STEEL BRAZIER



POWER MODULATION



REAR SMOKE OUTLET



“SILENT” FUNCTION



WEEKLY PROGRAMMING



REMOTE CONTROL WITH ROOM TEMPERATURE SENSOR

OPTIONAL



WI-FI



Black



White



Download on the App Store

GET IT ON Google Play