



IDRA 5S 5★

VENTILATED, PELLET FIRED, HYDRO STOVE



IDRA 5S		20	24
ENERGY CLASS		A+	A+
DIMENSIONS (WxDxH)	cm	59x68x122	59x68x122
HYDRO STOVE WEIGHT	kg	230	230
HEAT INPUT (min.-max.)	kW	6,8 - 20,1	8,4 - 24
NOMINAL HEAT OUTPUT (min.-max.)	kW	6,5 - 19,2	7,9 - 22,8
OUTPUT TO THE WATER (min.-max.)	kW	5,4 - 17,4	6,6 - 20,9
OUTPUT TO THE ENVIRONMENT (min.-max.)	kW	1,1 - 1,8	1,3 - 1,9
EXCHANGER WATER CONTENT	l	50	50
EXPANSION VESSEL	l	8	8
MAXIMUM OPERATING PRESSURE	bar	3	3
PUMP HEAD	m	6	6
WATER SIDE RESISTANCE (Δt 10 K) / (Δt 20 K)	mbar	123,5 / 30,9	186,8 / 46,7
EFFICIENCY (@ min.-max.)	%	95,9 - 95,6	94,9 - 94,2
MINIMUM CHIMNEY DRAUGHT	Pa	12	12
FLUE GAS DISCHARGE/AIR INTAKE DUCT DIAMETER	mm Ø	80 / 50	80 / 50
PELLET TANK CAPACITY	kg	38	38
PELLET CONSUMPTION min.-max.	kg/h	1,41 - 4,19	1,7 - 5,0
ELECTRIC ABSORPTION nominal/during ignition	W	72 - 320	83 - 345
HEATABLE VOLUME	m³	440	510
NOISE	dB	35 / 50	35 / 50

Ventilated pellet stove with an exclusive combustion system with high performance. IDRA 5S with its 5 stars is positioned at the top of the Environmental Certification. The presence of the “magic glass” and its linear style make it both elegant and versatile.

IDRA 5S

PRODUCT PLUS



HYDRO
VENTILATED



MAGIC
GLASS



AUTOMATIC
BRAZIER
CLEANING



POWER
MODULATION



REAR SMOKE
OUTLET



WEEKLY
PROGRAMMING

OPTIONAL



WI-FI
U-in



Black



White



Burgundy



APP-O BIOEN

Download on the
App Store

GET IT ON
Google Play