



IDRA 25-30

IDRA 25-30

VENTILATED PELLET HYDRO-STOVE



ECO
DESIGN
2022



IDRA		25	30
ENERGY CLASS		A+	A+
DIMENSIONS (LxPxH)	cm	60,4x61x122,1	60,4x61x122,1
WEIGHT	kg	225	225
NOMINAL INPUT (min.-max.)	kW	8,32 - 25,12	8,32 - 29,95
NOMINAL OUTPUT (min.-max.)	kW	8,04 - 23,4	8,04 - 27,8
OUTPUT TO THE WATER (min.-max.)	kW	6,73 - 20,61	6,73 - 24,64
OUTPUT TO THE ROOM (min.-max.)	kW	1,31 - 2,79	1,31 - 3,16
EXCHANGER WATER CONTENT	l	26,5	26,5
EXPANSION VESSEL CAPACITY	l	6	8
MAXIMUM WORKING PRESSURE	bar	1,5	1,5
MANOMETRIC HEAD OF THE PUMP	m	6	6
EFFICIENCY AT NOMINAL OUTPUT (min.-max.)	%	96,73 - 93,17	96,73 - 92,83
MINIMUM DRAUGHT AT THE CHIMNEY BASE	Pa	12	12
SMOKE OUTLET Ø	mm Ø	100	100
AIR INTAKE DIAMETER	mm	rectangular 50x100	rectangular 50x100
PELLET RESERVOIR CONTENT	kg	28	28
AVERAGE CONSUMPTION (min.-max.)	kg/h	1,71 - 5,18	1,71 - 6,17
ELECTRIC ABSORPTION	W	112	138
HEATING VOLUME	m ³	230 ÷ 670	230 ÷ 796

Ventilated pellet hydro-stove with steel cladding, equipped with an exclusive pellet dosing system which, thanks to the star shape with a sharp profile of its distributor, allows the quantity of fuel to be delivered precisely. The automatic brazier cleaning system is innovative and effectively simplifies the operations.

PLUS PRODUCT



HYDRO
VENTILATED



MAGIC
GLASS



AUTOMATIC
BRAZIER
CLEANING



POWER
MODULATION



REAR SMOKE
OUTLET



WEEKLY
PROGRAMMING

OPTIONAL



WI-FI



Black



White



Burgundy

