



OH S 34

WOOD LOGS FIRED BOILER WITH REVERSE FLAME



OH S 34

OH S		34
HEAT INPUT	kW	34,64
HEAT OUTPUT	kW	31,22
HEATING EFFICIENCY CLASS		A+
EFFICIENCY	%	90,12
CO ₂	%	14,7
MAX OPERATING PRESSURE	bar	3
MINIMUM DRAUGHT required by chimney	Pa	17
FLOW TEMPERATURE min./max.	°C	70 / 85
RETURN TEMPERATURE minimum	°C	55
COMBUSTION AUTONOMY	h	4
WOOD STORAGE VOLUME	l	100
LOG LENGTH	cm	50
FLUE GAS TEMPERATURE Qn	°C	161
Recommended thermal STORAGE VOLUME	l	>1200÷2000
DIMENSIONS (WxDxH)	mm	660x1285x1610
BOILER DRY WEIGHT	kg	557

(*) Power obtained with wood/pellet according to the standard ISO 17225-2 class A1-A2

High-performance log wood boiler thanks to reverse flame technology, equipped with regulation with optimized control of fuel gasification. The generous log wood storage magazine ensures long autonomy with a single fuel load.

PLUS PRODUIT



WOOD LOGS
FIRED
BOILER



FLAMME
INVERSEE



POWER
MODULATION



SOLAR CIRCUIT
CONTROL



ADJUSTABLE SMOKE
OUTLET

