

VENTILATED PELLET STOVE





ECO DESIGN 2022







CLEA		8	10C ducted	15C ducted
ENERGY CLASS		A+	A+	A+
DIMENSIONS (WxDxH)	cm	49x54x111	49x54x111	49x54x111
STOVE WEIGHT	kg	100	100	100
HEAT INPUT (minmax.)	kW	3,2 - 9	3,2 - 11,1	5,3 - 15,3
HEAT OUTPUT (minmax.)	kW	3,1 - 8,1	3,1 - 9,9	4,9 - 13,6
EFFICIENCY (@ minmax.)	%	94,5 - 90,7	94,5 - 88,9	93,4 - 88,7
MINIMUM CHIMNEY DRAUGHT	Pa	12	12	12
FLUE GAS EXHAUST DIAMETER	mm Ø	80	80	80
AIR INTAKE DUCT DIAMETER	mm Ø	50	50	50
PELLET TANK CAPACITY	kg	22	22	22
PELLET CONSUMPTION minmax.	kg/h	0,67 - 1,85	0,67 - 2,30	1,09 - 3,17
Nominal ELECTRICAL ABSORPTION	W	40,1	91,6	94,2
ELECTRICAL ABSORPTION during ignition	W	281	281	281
HEATABLE VOLUME	m³	180	220	300

A pellet stove with a modern design and ceramic inserts that enhance its elegance and prestige. Side panels in black steel and hearth front door in Night View type glass for a greater scenic effect even when the stove is switched off. Equipped with blown self-cleaning system that guarantees cleaning and constant combustion efficiency. Quartz igniter for quick ignition. With the hand-held remote control and integrated room sensor, optimum management of room temperature as well as various functions is possible. The combustion chamber, made entirely of vermiculite, guarantees excellent performance. Selfcleaning glass with dedicated air. The "controlled negative pressure" operation and all installed devices ensure maximum comfort in complete safety. The versatility of the ducting system (mod. 10C-15C), allows optimal warmth also in other rooms of the house.

PRODUCT PLUS



VENTILATED STOVE



DUCTED (mod. 10C-15C)



NIGHT VIEW GLASS



STEEL **BRAZIER**



POWER MODULATION



REAR SMOKE OUTLET



RADIO CONTROL WITH ROOM PROBE



(mod. 15C)

IGNITER



DAILY / WEEKLY **PROGRAMMING**

U-in



"SILENT" **FUNCTION**





OPTIONAL



AIR IONISER



ROOM TEMP. PROBE (mod. 10C-15C)









