



ADNA S 5★

VENTILATED PELLET STOVE



ADNA

ADNA		8S	10SC ducted	12SC ducted
ENERGY CLASS		A+	A+	A+
DIMENSIONS (WxDxH)	cm	58x59x112	58x59x112	58x59x112
STOVE WEIGHT	kg	120	120	120
HEAT INPUT (min.-max.)	kW	3,2 - 9	3,2 - 11,1	3,2 - 12,1
HEAT OUTPUT (min.-max.)	kW	3,1 - 8,1	3,1 - 9,9	3,1 - 10,7
EFFICIENCY (@ min.-max.)	%	94,5 - 90,7	94,5 - 88,9	94,5 - 88,2
MINIMUM CHIMNEY DRAUGHT	Pa	12	12	12
FLUE GAS EXHAUST DIAMETER	mm Ø	80	80	80
AIR INTAKE DUCT DIAMETER	mm Ø	50	50	50
PELLET TANK CAPACITY	kg	20	20	20
PELLET CONSUMPTION min.-max.	kg/h	0,67 - 1,85	0,67 - 2,30	0,67 - 2,51
Nominal ELECTRICAL ABSORPTION	W	40,1	91,6	95,2
ELECTRICAL ABSORPTION during ignition	W	281	281	281
HEATABLE VOLUME	m³	210	260	320

A pellet stove with a circular design and ceramic inserts that enhance its elegance and prestige. Rounded sides in black steel and hearth glass of "Magic" type, beyond the fire door, for a greater scenic effect even when the stove is switched off. Equipped with blown self-cleaning system that guarantees cleaning and constant combustion efficiency. Quartz igniter for quick ignition. With the hand-held remote control and integrated room sensor, optimum management of room temperature as well as various functions is possible. The combustion chamber, made entirely of vermiculite, guarantees excellent performance. Self-cleaning glass with dedicated air. The "controlled negative pressure" operation and all installed devices ensure maximum comfort in complete safety. The versatility of the ducting system (mod. 10C-13C), allows optimal warmth also in other rooms of the house.

PRODUCT PLUS



VENTILATED
STOVE



DUCTED
(mod. 10SC-12SC)



MAGIC
GLASS



STEEL
BRAZIER



POWER
MODULATION



TOP
FITTING
130/80



TOP SMOKE
OUTLET



RADIO CONTROL
WITH ROOM
PROBE



DAILY /
WEEKLY
PROGRAMMING



"SILENT"
FUNCTION



QUARTZ
IGNITER



HERMETIC



WI-FI
U-in

OPTIONAL



ROOM TEMP.
PROBE
(mod. 10SC-12SC)



Black



White



APP-O BIOEN

Download on the
App Store

GET IT ON
Google Play