



ZENA 5★

VENTILATED PELLET STOVE



ZENA

ZENA		9	11	11C ducted	13C ducted
ENERGY CLASS		A+	A+	A+	A+
DIMENSIONS (WxDxH)	cm	49x56x110	49x56x110	49x56x110	49x56x110
STOVE WEIGHT	kg	100	100	100	105
HEAT INPUT (min.-max.)	kW	3,2 - 9	3,2 - 11,1	3,2 - 11,1	5,3 - 13,6
HEAT OUTPUT (min.-max.)	kW	3,1 - 8,1	3,1 - 9,9	3,1 - 9,9	4,9 - 12,2
EFFICIENCY (@ min.-max.)	%	94,5 - 90,7	94,5 - 88,9	94,5 - 88,9	93,4 - 89,5
MINIMUM CHIMNEY DRAUGHT	Pa	12	12	12	12
FLUE GAS EXHAUST DIAMETER	mm Ø	80	80	80	80
AIR INTAKE DUCT DIAMETER	mm Ø	50	50	50	50
PELLET TANK CAPACITY	kg	22	22	22	22
PELLET CONSUMPTION min.-max.	kg/h	0,67 - 1,85	0,67 - 2,30	0,67 - 2,30	1,09 - 2,82
Nominal ELECTRICAL ABSORPTION	W	40,1	41,6	91,6	93,4
ELECTRICAL ABSORPTION during ignition	W	281	281	281	281
HEATABLE VOLUME	m³	180	220	220	270

Steel-clad pellet stove, elegant and modern also thanks to rounded sides and front. Equipped with a blown self-cleaning system that guarantees cleanliness and constant combustion efficiency and a quartz igniter for fast ignition. With the hand-held remote control and integrated room sensor, optimum management of room temperature as well as various functions is possible.

The combustion chamber, made entirely of vermiculite, guarantees excellent performance. Self-cleaning ceramic glass with dedicated air. The “controlled negative pressure” operation and all installed devices ensure maximum comfort in complete safety.

The versatility of the ducting system (mod. 11C-13C), allows optimal warmth also in other rooms of the house.

PRODUCT PLUS



VENTILATED
STOVE



DUCTED
(mod. 11C-13C)



CERAMIC
GLASS



STEEL
BRAZIER



POWER
MODULATION



REAR SMOKE
OUTLET



RADIO CONTROL
WITH ROOM
PROBE



HERMETIC
(mod. 13C)



DAILY /
WEEKLY
PROGRAMMING



“SILENT”
FUNCTION



QUARTZ
IGNITER



WI-FI
U-in

OPTIONAL



AIR
IONISER



Black



White



Burgundy



APP-O BIOEN

Download on the
App Store

GET IT ON
Google Play